



QuikTurn™ 360 Turning Target System

The QuikTurn 360 provides extensive, comprehensive live fire training, emphasizing unpredictable situations.

Designed for random and concealed placements throughout an indoor or outdoor live-fire range, the QuikTurn 360 can be configured to fully enhance training.

- 90° expose/conceal time less than .5 seconds.
- 360° target presentations, advanced target identification threat/non-threat target engagements.
- All targets can be controlled in unison/collectively or individually controlled.
- Red, blue and white light LED light.
 - Hostile fire mode – white light.
 - Distraction lighting – red/blue light.
- Quiet electronic turning motor eliminates audible identification of turning targets.
- Eliminates maintenance associated with pneumatic components.
- 600 round per minute hit sensing (ground mount unit only) with hit sensing head using molded targets. System can identify hits for both friend and foe target engagements.
- Supports multiple target heads and existing customer target frames such as: Rebar, 1"x2" wood upright and molded 3D targets.
- Qualifications and advanced training scenarios can be authored, stored and accessed any time using the RangeMaster™ 9K/10K software and wireless tablet.



Technical Specifications	
Hit Sensing	Up to 600 hits/minute (ground mount only)
Actuations and Hit Modes	Expose, conceal, 15° and 90° rotation up to 360°
LED Lights	Red, blue and white
90° Expose/Conceal Time	Less than .5 seconds
360° Turn Time	Less than 1 second
Target Size	Holds multiple target types
Max Target Weight	10 pounds
Weight of Unit	11 lbs. (5 kg)
Overhead Target Shaft Length	3 feet (custom lengths available)
Actuator Enclosure Dim	8.25" x 13.5" x 9.0"
Power Supply	AC Power 120/240 VAC at 50/60Hz
Max Current Draw Per Target	1 amp @ 120 VAC

